

EXHIBIT A

Required Interisland Livestock Shipping Standards | CATTLE

SHIPPING METHOD	Trailers, 20' containers, 40' containers, shipping pens. Must be 4-sided, structurally sound and without protruding objects that could injure animals. Must have four sided forklift pockets to ensure container cannot shift or tip off the fork lift during lifting.
LEAK PROOF	All shipping trailers/containers shall be watertight up to a level of 2" and nonslip flooring is required.
SIDES	Sides shall be solid up to the level of the animals' backs or window guards should be indented to prevent discharge.
WINDOWS	Escape proof. Must contain entire animal. Tall enough to be above the backs of the animals or with 6" indented bars to prevent fecal discharge and allow proper airflow* *Window openings should be at least 7% of the area of the side panel surface to ensure proper ventilation
ROOF	Must have a solid roof to protect from the sun, rain, and contain the animal entirely.
WATER	Not required for trips < 24hrs; must have some form of watering system in case of transit delay. Please bring your own water when possible.
FEED	Not required for trips < 24hrs.
SPACE	*See table.
TRAILERS DELIVERING LIVESTOCK	All livestock trailers entering into the harbor must be constructed to contain animal fecal matter and urine.
TRANSFER AREA & STAGING AREA	In secured DOT designated area only. Water should be available nearby.
TRANSFER PROCESS (TRAILER TO CONTAINER)	Trailer with slide or inward opening gate abut flush to container with slide or inward opening gates.
OR TRANSFER PROCESS (DOT CHUTE)	Secure chute gates to trailer and container, if DOT chute is available.
SPILLAGE	All spillage must be cleaned up and removed from harbor. To comply with EPA, no water should be used to clean, the shipper must bring shovel, broom, etc to clean area. All shipping containers that remain in the harbor must be cleaned out and material hauled away. A fine/fee will be imposed if spillage is not cleaned.

*These space requirements only pertain to Hawaii interisland transportation and do not pertain to interstate shipping.

AVG. BODYWEIGHT (lbs)	AREA PER ANIMAL (ft ²)	HEIGHT (ALL SPECIES)	20' CONTAINER (max number to load)	40' CONTAINER (max number to load)	40'X2 DOUBLEDECKER (w/ feeders and water units) (max number to load)
400	6.5	Stand comfortably, ensure head clearance	23	46	70
500	7.5		20	40	61
600	8.5		17	36	54
800	10.4		14	29	Over height limit
1,000	13		11	23	Over height limit
1,200	14.7		10	21	Over height limit
1,400	18		8	17	Over height limit

Required Interisland Livestock Shipping Standards | Sheep/ Goats

SHIPPING METHOD	Trailers, 20' containers, 40' containers, shipping pens. Must be structurally sound and without protruding objects that could injure animals. Must have four sided forklift pockets to ensure container cannot shift or tip off the fork lift during lifting.
LEAK PROOF	All shipping trailers/containers shall be watertight up to a level of 2" minimum absorptive bedding and nonslip flooring is required.
SIDES	Sides shall be solid up to the level of the animals' backs.
WINDOWS	Escape proof. Must contain entire animal. Tall enough to be above the backs of the animals or with 3" indented bars to prevent fecal discharge.
ROOF	Must have a solid roof to protect from the sun, rain, and contain the animal entirely.
WATER	Not required for trips < 24hrs; must have some form of watering system in case of transit delay. Please bring your own water when possible.
FEED	Not required for trips < 24hrs.
SPACE	*See table.
TRAILERS DELIVERING LIVESTOCK	All livestock trailers entering into the harbor must be constructed to contain animal's fecal matter and urine, and contain bedding material.
TRANSFER AREA & STAGING AREA	In DOT designated area only. Water should be available nearby.
TRANSFER PROCESS (TRAILER TO CONTAINER)	Trailer with slide or inward opening gate abut flush to container with slide or inward opening gates.
OR TRANSFER PROCESS (DOT CHUTE)	Secure chute gates to trailer and container, if DOT chute is available. Block space between trailer back gate floor and ground.
SPILLAGE	All spillage must be cleaned up and removed from harbor. To comply with EPA, no water should be use to clean, the shipper must bring shovel, broom, etc to clean area. All shipping containers that remain in the harbor must be cleaned out and material hauled away. A fine/fee will be imposed if spillage is not cleaned.

*These space requirements only pertain to Hawaii interisland transportation and do not pertain to interstate shipping.

AVG. BODY WEIGHT (lbs)	AREA PER ANIMAL (ft ²)	HEIGHT (ALL SPECIES)	20' CONTAINER (max number to load)	40' CONTAINER (max number to load)	40'X2 DOUBLEDECKER (w/o feeders and water units) (max number to load)
60	2.2	Stand comfortably, ensure head clearance	67	137	240
80	2.5		59	121	211
100	2.8		53	107	189
120	3.4		44	89	156